



**Creation
Clic Acoustic**

Gerflor®

Creation

click Acoustic

Design
without
limits

Harmony

Combine tiles & planks to create a coordinated floor scheme

Perfectly complements Gerflor wall covering solutions



Comfort & well being

- Improved walking comfort
- Enhanced sound insulation properties
- Warm feeling underfoot



Sustainability

- Made in Europe since 1985
- Recycled content up to 55%
- 100% recyclable
- Part of Gerflor Second Life Program



30 core designs

Already available in
Creation 40 & 55
Clic Acoustic


Get ready for
the full collection
in January 2026!



Floor: Bloom Uni Cream 1600 / Wall: Mural Revela Hanoi 7918



Lounge Oak



Lounge Oak Beige 1272
XL plank



Lounge Oak Golden 1271
XL plank



Lounge Oak Natural 1273
XL plank



Lounge Oak Chesnut 1274
XL plank



Design shade variation:  Light  Medium  High





Lounge Oak Natural 1273





Cedar

 XL Plank
  Ultra realistic embossing




Cedar Natural 1607
XL plank 



Cedar Golden 1606
XL plank 



Cedar Brown 0850
XL plank 



Cedar Dark Brown 1605
XL plank 

Design shade variation:  Light  Medium  High

Cedar Dark Brown 1605

Tamo


Ultra realistic
embossing



Tamo Cream 1598
Standard plank



Tamo Light Brown 1568
Standard plank



Tamo Natural 1561
Standard plank



Tamo Clear 1567
Standard plank



Design shade variation:  Light  Medium  High



Tamo Natural 1561



Quartet Natural 0545

Quartet

Ultra realistic
embossing



Quartet Natural 0545
Standard plank



Quartet Honey 0870
Standard plank



Quartet 0503
Standard plank



Quartet Dark Brown 1597
Standard plank

Design shade variation: Light Medium High

Bostonian Oak


Ultra realistic
embossing



Bostonian Oak Honey 0851
Standard plank



Bostonian Oak Beige 0853
Standard plank



Design shade variation:  Light  Medium  High



Bostonian Oak Beige 0853



White Lime 0584

Timeless Design



White Lime 0584
Standard plank



Ranch 0456
Standard plank



Ranch 0456



Long Board 0455
Standard plank



Long Board 0455

Design shade variation:  Light  Medium  High

Timeless Design


Ultra realistic
embossing



Ballerina 0347
Standard plank



Honey Oak 0441
Standard plank



Twist 0504
Standard plank



Honey Oak 0441



Ballerina 0347



Twist 0504

Design shade variation:  Light  Medium  High



Curton Stone Clear 1603

Curton Stone



Curton Stone Taupe 1604
Rectangular tile



Curton Stone Clear 1603
Rectangular tile



Design shade variation:  Light  Medium  High

Bloom Uni



Bloom Uni Cream 1600
Rectangular tile



Bloom Uni Clear 1599
Rectangular tile



Bloom Uni Pearl 1602
Rectangular tile



Bloom Uni Dark 1601
Rectangular tile



Design shade variation:  Light  Medium  High



Bloom Uni Cream 1600

Cross References

Color Code	Color Design	Available	
		Creation 40 Clic Acoustic	Creation 55 Clic Acoustic
0347	Ballerina	212x1239mm	212x1239mm
1599	Bloom Uni Clear	389x729mm	389x729mm
1600	Bloom Uni Cream	389x729mm	389x729mm
1601	Bloom Uni Dark	389x729mm	389x729mm
1602	Bloom Uni Pearl	389x729mm	389x729mm
0853	Bostonian Oak Beige	212x1239mm	212x1239mm
0851	Bostonian Oak Honey	212x1239mm	212x1239mm
0850	Cedar Brown	240x1461mm	240x1461mm
1605	Cedar Dark Brown	240x1461mm	240x1461mm
1606	Cedar Golden	240x1461mm	240x1461mm
1607	Cedar Natural	240x1461mm	240x1461mm
1603	Curton Stone Clear	389x729mm	389x729mm
1604	Curton Stone Taupe	389x729mm	389x729mm
0441	Honey Oak	212x1239mm	212x1239mm
0455	Long Board	212x1239mm	212x1239mm
1272	Lounge Oak Beige	240x1461mm	240x1461mm
1274	Lounge Oak Chestnut	240x1461mm	240x1461mm
1271	Lounge Oak Golden	240x1461mm	240x1461mm
1273	Lounge Oak Natural	240x1461mm	240x1461mm
0503	Quartet	212x1239mm	212x1239mm
1597	Quartet Dark Brown	212x1239mm	212x1239mm
0870	Quartet Honey	212x1239mm	212x1239mm
0545	Quartet Natural	212x1239mm	212x1239mm
0456	Ranch	212x1239mm	212x1239mm
1567	Tamo Clear	212x1239mm	212x1239mm
1598	Tamo Cream	212x1239mm	212x1239mm
1568	Tamo Light Brown	212x1239mm	212x1239mm
1561	Tamo Natural	212x1239mm	212x1239mm
0504	Twist	212x1239mm	212x1239mm
0584	White Lime	212x1239mm	212x1239mm

Available in 2026				
Creation 30 Dry Back	Creation 40 Dry Back	Creation 40 Clic	Creation 55 Dry Back	Creation 55 Clic
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
457x914mm	457x914mm	-	457x914mm	-
457x914mm	457x914mm	-	457x914mm	-
457x914mm	457x914mm	-	457x914mm	-
457x914mm	457x914mm	-	457x914mm	-
184x1219mm	184x1219mm	-	184x1219mm	-
184x1219mm	184x1219mm	-	184x1219mm	-
230x1500mm	230x1500mm	240x1461mm	230x1500mm	240x1461mm
230x1500mm	230x1500mm	240x1461mm	230x1500mm	240x1461mm
230x1500mm	230x1500mm	240x1461mm	230x1500mm	240x1461mm
230x1500mm	230x1500mm	240x1461mm	230x1500mm	240x1461mm
457x914mm	457x914mm	389x729mm	457x914mm	389x729mm
457x914mm	457x914mm	389x729mm	457x914mm	389x729mm
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
230x1500mm	230x1500mm	240x1461mm	230x1500mm	240x1461mm
230x1500mm	230x1500mm	240x1461mm	230x1500mm	240x1461mm
230x1500mm	230x1500mm	240x1461mm	230x1500mm	240x1461mm
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
184x1219mm	184x1219mm	-	184x1219mm	-
184x1219mm	184x1219mm	-	184x1219mm	-
184x1219mm	184x1219mm	-	184x1219mm	-
184x1219mm	184x1219mm	-	184x1219mm	-
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm
184x1219mm	184x1219mm	212x1239mm	184x1219mm	212x1239mm




Available in 2026			
Creation 70 Dry Back	Creation 70 Clic	Skirting Color code	Coverstrip Color code
208x1243mm	212x1239mm	S008	C008
-	-	S094	C017
-	-	S204	C020
-	-	S092	C015
-	-	S096	C016
-	-	S017	C013
-	-	S019	C006
230x1500mm	240x1461mm	S024	C001
230x1500mm	240x1461mm	S203	C001
230x1500mm	240x1461mm	S202	C003
230x1500mm	240x1461mm	S025	C002
457x914mm	389x729mm	S184	C020
457x914mm	389x729mm	S178	C021
208x1243mm	212x1239mm	S033	C006
208x1243mm	212x1239mm	S034	C006
230x1500mm	240x1461mm	S168	C002
230x1500mm	240x1461mm	S192	C004
230x1500mm	240x1461mm	S189	C003
230x1500mm	240x1461mm	S189	C008
208x1243mm	212x1239mm	S056	C003
208x1243mm	212x1239mm	S073	C024
208x1243mm	212x1239mm	S058	C008
208x1243mm	212x1239mm	S132	C003
208x1243mm	212x1239mm	S053	C014
-	-	S168	C006
-	-	S193	C005
-	-	S202	C003
-	-	S016	C004
208x1243mm	212x1239mm	S039	C011
208x1243mm	212x1239mm	S074	C025

S001 : White / Blanc
S001 : Aluminium



Curton Stone Taupe 1604

Technical Data

		Creation 40 Clic Acoustic			Creation 55 Clic Acoustic			
Description / Beschreibung / Beschrijving / Descripción / Descrição / Descrizione								
Épaisseur totale / Total Thickness / Gesamtdicke / Totale dikte / Espesor total / Espessura total / Spessore totale	EN ISO 24346	mm	5.50			6.00		
Épaisseur couche d'usure / Thickness of the wearlayer / Dicke der Nuttschicht / Dikte van de slijtlaag / Espesor capa de uso / Espessura camada de desgaste / Spessore strato di usura	EN ISO 24340	mm	0.40			0.55		
Poids / Weight / Flächengewicht / Gewicht / Peso / Peso / Peso	EN ISO 23997	g/m²	7229			8024		
Format / Size / Format / Afmetingen / Dimensiones / Dimensões / Dimensione	EN ISO 24342	mm	212 × 1238.8	239.6 × 1460.8	388.8 × 728.7	212 × 1238.8	239.6 × 1460.8	388.8 × 728.7
Nombre de lames/dalles - m² par boîte / Number of planks & tiles - m² per box	-	-	8 / 2.10	6 / 2.10	7 / 1.98	7 / 1.84	5 / 1.75	6 / 1.70
Sans phtalates / Phthalate free / Phthalatfrei / Sin ftalatos / Sem ftalatos / Senza ftalati	-	-	OK			OK		
Classification / Klassifikation / Classificatie / Clasificaciones / Classificações / Classificazioni								
Norme/Spécification produit / Norm/Product Specification / Produktnorm / Technische eigenschappen / Normas / Normas / Norma prodotto	-	-	EN ISO 10582			EN ISO 10582		
Classement européen / European Classification / Europäische Klassifizierung / Europese classificatie / Clasificación europea / Classificação Europeia / Europea	EN ISO 10874	class	23 – 32			23 – 33 – 42		
Certification  (evaluation.cstb.fr)	QB 30	n° certif.	-			-		
Avis Technique	-	n° AT.	-			-		
Classement Feu / Fire Rating / Brandverhalten / Brand classificatie / Fuego / Fogo / Reazione al fuoco	EN 13501-1	class	Bfl-s1			Bfl-s1		
Potentiel de charge / Static Electrical Propensity / Begehaufadung / Elektrische eigenschappen / Comportamiento electrostático / Comportamento electrostático / Resistenza elettrica	EN 1815	kV	< 2			< 2		
Glissance humide / Slip Resistance Wet / Rutschhemmung / Anti-slip / Deslizamiento húmedo / Escorregamento húmido / Scivolosità umida ⁽¹⁾	DIN 51130	class	R10			R10		
Performances / Technische eigenschappen / Testresultaat / Cualidades técnicas / Performances / Caratteristiche tecniche								
Résistance à l'usure / Wear Resistance / Verschleißverhalten / Slijtvastheid / Abrasión / Abrasão / Resistenza all'abrasione	EN 660.2	mm³	≤ 2.0			≤ 2.0		
Groupe d'abrasion / Wear Group / Verschleißgruppe / Groep slijtvastheid / Grupo de abrasión / Grupo de abrasão / Gruppo di abrasione	QB 30	group	T			T		
Teneur en agent liant / Type Binder content / Bindemittelgehalt / Contenido en ligante / Conteúdo em ligante	EN ISO 10582	type	I			I		
Stabilité dimensionnelle (norme) / Dimensional stability (norm) / Maßstabilität (Norm) / Maatvastheid (norm) / Estabilidad Dimensional (Exigencia) / Estabilidade dimensional (normalização) / Stabilità dimensionale (requisito normativo)	EN ISO 23999	%	≤ 0.15			≤ 0.15		
Stabilité dimensionnelle (valeur moyenne mesurée) / Dimensional stability (average measured value) / Maßstabilität (Durchschnittsmesswert) / Maatvastheid (gemeten gemiddelde waarde) / Estabilidad Dimensional (Valor medido) / Estabilidade Dimensional (Valor medio) / Stabilità dimensionale (rilevata)	-	%	≈ 0.05			≈ 0.05		
Isolation acoustique bruits de chocs / Impact sound insulation / Trittschallverbesserungsmaß / Geluidsisolatie / Acústica / Isolamento acústico	EN ISO 717-2	dB	19			19		
Sonorité à la marche / Room Impact / Raumschall / Loopgeluid / Rumore al calpestio / Sonoridad en la pisada / Sonoridade ao andar	NF S 31074	dB	79			79		
Poinçonnement statique rémanent / Residual Indentation / Resteindruck / Indrukbelasting / Punzonamiento / Punçoamento / Impronta	EN ISO 24343-1	mm	-			-		
Essai de la chaise à roulettes / Castor chair test / Stuhlrollenbeanspruchung / Rolweerstand bureaustoelen / Determinación del efecto de una silla con ruedas / Resistência a cadeiras de rodas / Resistenza al passaggio di sed (type H)	ISO 4918	-	OK			OK		
Conductivité thermique / Thermal Conductivity / Wärmeleitfähigkeit / Thermische weerstand / Conductividad térmica / Contutividade térmica / Resistenza termica / Värmeledningsmotstånd / Värmemotstånd	EN ISO 10456	W/(m.k)	0.25			0.25		
Solidité lumière / Colour Fastness / Lichtechtheid / Lichtechtheid / Resistencia a la luz / Estabilidade das cores / Solidità alla luce	EN 20 105-B02	degree	≥ 6			≥ 6		
Résistance aux produits chimiques / Chemical Products Resistance / Verhalten gegenüber Chemikalien ⁽²⁾ / Chemische bestendigheid / Resistencia a los productos quimicos / Resistência aos produtos quimicos / Resistenza ai prodotti chimici	EN ISO 26987	-	OK			OK		
Traitement de surface / Surface Treatment / Oberflächenvergrüfung / Oppervlaktebehandeling / Tratamiento de superficie / Tratamento de superficie	-	-	ProtecShield™			ProtecShield™		
Environnement / Umwelt / Medio ambiente / Ambiente / Ambiente								
Contenu recyclé / Recycled content	-	%	up to / jusqu'à 55%			up to / jusqu'à 55%		
Recyclabilité / Recyclability	-	%	100			100		
FDES / EPD	-	-	Available / Disponible			Available / Disponible		
Santé / Health / Gesundheit / Salud / Saúde / Salute								
TCOV après 28 jours / TVOC after 28 days / TVOC (28 Tage) / TVOC (28 dagen) / TVOC (28 dias) / TVOC (28 dias) / TVOC (28 giorni) / TVOC (28 dagar) / TVOC (28 dager)	ISO 16000-6	micrograms/m³	< 10			< 10		
Certification	-	-	-			-		
Marquage CE / CE Marking / CE Kennzeichnung / Eg_conformiteitsmerk / Marca De Conformidad CE / Marca DE Conformidade CE / Marcatura CE Di Conformita								
	EN 14041							

(1) Plan incliné avec huile / Ramp test with oil / Schiefe Ebene

(2) Beständig gegenüber nicht färbenden alkoholhaltigen Handdesinfektionsmitteln, Haushaltschemikalien und verdünnten Säuren und Laugen bei kurzzeitiger Einwirkung.

IMPORTANT: The information contained in this document is valid from 01/04/2025 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

we care / we act Our Commitments for a Sustainable future



CARBON FOOTPRINT*
-20 % kg
CO₂ equivalent/m²
between 2020 and 2025



BIOSOURCED CONTENT**
10 % by 2025



RECYCLED CONTENT
30 % by 2025



ADHESIVE FREE***
35 % by 2025



ANNUAL VOLUME RECYCLED
60 000 t by 2025



* Scopes 1 and 2 defined in the GHG protocol ** % of activity with biosourced materials *** % of activity - adhesive free solution